

BOP Anular

SEP annular BOP is offered in a variety of sizes and pressure ratings. All the annular BOP's offered by SEP are designed and manufactured to conform to API 16A specification, 3rd edition. All annular BOP's provided by SEP are rated for H₂S service.



Specification

Model	FH18-21	FH18-35	FH18-35/70	FH23-21	FH23-35	FH28-21	FH28-35	FH28-35/70	FH28-70/105	FH35-35	FH35-35/70	FH35-70/105	FH53-21	FH54-14
Working Pressure (psi)	3000	5000	5000	3000	5000	3000	5000	5000	10,000	5000	5000	10,000	3000	2000
Ring Groove	R45	R46	R46 BX156	R49	R50	R53	R54	R54 BX158	BX158	BX160	BX160 BX159	BX159	R74	R73
Bore size (in)	7/1/2016	7/1/2016	7/1/2016	9	9	11	11	11	11	13-5/8	13-5/8	13-5/8	20-3/4	21-1/4
Type	B	B	B	B	B	B	B	B	W	B	B	W	W	M
Gal. to Open	3.5	3.3	3.3	6	8.7	7.2	14.8	14.8	24.8	18.2	18.2	327	27.5	22.5
Gal. to Close	4.9	4.6	4.6	8.9	11.1	11.1	19.2	19.2	30.6	24.8	24.8	40.1	44.2	35.3
Hydraulic Connection NPT	1"	1"	1"	1"	1"	1"	1"	1"	1"	1"	1"	1"	1"	1"
Top Connection	Studded													
Bottom Connection	Flanged													
Height (in)	29	31	32	33	37	39	42	43	55	45	48	61	52	46
Length (in)	29	29	29	35	40	40	45	48	57	50	50	65	59	49

Weight (lbs.)	289 3	3212	3418	5275	6734	6921	9460	10,626	23,980	13,508	13,937	33,176	14,950	14,950
------------------	----------	------	------	------	------	------	------	--------	--------	--------	--------	--------	--------	--------

